



NYLON-INSULATED SPADE TERMINALS 尼龙Y型绝缘端子



PART NO 2015-2018	ITEM NO	WIRE RANGE		DIMENSIONS							COLOR
		AWG/MCM	mm <sup>2</sup>	ΦE	ΦD	Φd	W	B	L		
LY0021-3001	NL1.25-3YS	22-16	0.25-1.65	3.7	4.3	1.7	5.7	11.3	22.7	RED	
LY0021-3002	NL1.25-3YSA			3.2	4.3	1.7	5.7	11.3	22.7		
LY0021-3003	NL1.25-3YW			3.7	4.3	1.7	6.2	11.3	22.7		
LY0021-3004	NL1.25-4YS			4.3	4.3	1.7	6.4	11.3	22.7		
LY0021-3005	NL1.25-4YW			4.3	4.3	1.7	7.2	11.3	22.7		
LY0021-3006	NL1.25-5Y			5.3	4.3	1.7	8.0	11.3	22.7		
LY0021-3007	NL1.25-6Y			6.7	4.3	1.7	10.7	11.3	22.7		
LY0021-3008	NL2-3YS			16-14	1.04-2.63	3.7	5.0	2.3	5.7	11.3	22.7
LY0021-3009	NL2-3YSA	3.2	5.0			2.3	5.7	11.3	22.7		
LY0021-3010	NL2-3YW	3.7	5.0			2.3	6.2	11.3	22.7		
LY0021-3011	NL2-4YS	4.3	5.0			2.3	6.4	11.3	22.7		
LY0021-3012	NL2-4YW	4.3	5.0			2.3	7.2	11.3	22.7		
LY0021-3013	NL2-5Y	5.3	5.0			2.3	8.0	11.3	22.7		
LY0021-3014	NL2-6Y	6.7	5.0			2.3	10.7	11.3	25.7		
LY0021-3015	NL5.5-3Y	12-10	4.60-6.64			3.7	6.6	3.5	8.2	14.1	27.1
LY0021-3016	NL5.5-4Y			4.3	6.6	3.5	8.2	14.1	27.1		
LY0021-3017	NL5.5-5Y			5.3	6.6	3.5	9.0	14.1	27.1		
LY0021-3018	NL5.5-6Y			6.4	6.6	3.5	12.0	14.1	31.8		
LY0021-3019	NL8-5Y	8	8.64-10.52	5.3	8.0	4.5	9.0	16.0	30.9	RED	
LY0021-3020	NL8-6Y			6.7	8.0	4.5	12.0	16.0	31.4		